

ARCOR®
EPOXY TECHNOLOGIES™
ARCOR Epoxy Inc.
 PO Box 273 So. Dennis, MA 02660
 Tel:800-878-9593 Fax: 888-878-9593

Material Safety Data Sheet

Material

EE-121 Activator

Date Prepared

11/03

Emergency Telephone	Day: 800-878-9593
	Night: 800-878-9593

Health Hazard Data

CAS No.	Hazardous Ingredients	ACGIH	OSHA
1477-55-0	Benzene-1-3-Dimethaneamine	NA	NA
66402-68-4	Ceramic Microspheres	NA	NA
13463-67-1	Titanium Dioxide	NA	NA
14808-60-7	Quartz Silica	NA	NA

The remaining components are a trade secret

Physical/Chemical Characteristics

Boiling Point	480°F	Vapor Density	NA
Specific Gravity	1.12	Evaporation Rate	Less Than
Solubility in Water	Slight (0.1-1.0%)		
Vapor Pressure	5.50 @ 70°F	Melting Point	NA
Appearance & Odor	Straw Yellow liquid, Amoniacal Odor		

Effects of Overexposure

Ingestion: Low acute oral toxicity.

Eye Contact: Extremely irritating with possible eye injury.

Skin Contact: Overexposure could cause burns and blistering.

Skin Absorption: Not likely to be absorbed through skin in toxic amounts

Inhalation: Not considered a problem unless heated to high temperature.

Emergency and First Aid Procedures

Skin: Wash with soap and water; wash clothes before reuse

Ingestion: DO NOT INDUCE VOMITING. Give one glass of water unless victim is drowsy, convulsing, or unconscious. Seek medical attention immediately.

Inhalation: Remove to fresh air if effects occur; consult physician.

Eyes: Irrigate with water for fifteen minutes; consult physician.

Spill or Leak Procedure

Steps to be Taken if Release or Spilled

Absorb with inert material (sand, vermiculate, Ect.), sweep or scoop up and put in disposal container. Flush area immediately with plenty of water; prevent washings from entering waterways.

Waste Disposal Method

Incinerate in furnace or bury in landfill in accordance with Federal, State & Local Regulations.

Precautions For Safe Handling and use

Flash Point

>212° F (closed cup)

Flammable Limits

LEL: not available UEL: not available

Extinguishing Media

Use Water spray, Dry chemical, foam or Carbon Dioxide

Special Fire Fighting Procedures

Treat as a class B fire. Use water to cool containers

Special Protection Information

Respiratory Protection

NIOSH approved organic vapor respirators are only required when ventilation is inadequate. NIOSH approved air-line respirators with auxiliary escape air tanks or self-contained breathing apparatus should be used in confined spaces.

Ventilation

Local mechanical exhaust

Protective Gloves

Impervious gloves

Eye Protection

Safety Glasses with side shields.

Other Protective Equipment

Safety shower and eye bath should be provided. Use coveralls or apron to protect against skin and clothing contamination.

Reactivity Data

Stability

Stable

Incompatibility (materials to avoid)

Keep away from open flame. Prior to cure, avoid contact with oxidizing agents

Hazardous Decomposition Products

Decomposition may produce Carbon Monoxide and/or Carbon Dioxide

Hazardous Polymerization

Will not occur

Conditions To Avoid

Oxidizing materials

Special Precautions

Precautions to be taken in Storage and handling

Practice reasonable care and cleanliness

Other Precautions

Avoid gross contamination of skin. Wash with plenty of soap and water. Use with adequate ventilation. Avoid breathing vapors

ARCOR®
EPOXY TECHNOLOGIES™
ARCOR Epoxy Inc.
 PO Box 273 So. Dennis, MA 02660
 Tel:800-878-9593 Fax: 888-878-9593

Material Safety Data Sheet

Material **EE-121 Base**

Revision 11/03

Health Hazard Data

Effects of Overexposure
Ingestion: Low acute oral toxicity; LD50 (RAT) greater than 2000 MG/KS.
Eye Contact: Minor transient irritation. No corneal injury likely.
Skin Contact: Only minor irritation. May be a skin sensitizer.
Skin Absorption: Not likely to be absorbed through skin in toxic amounts.
Inhalation: Not considered a problem unless heated to high temperature.
Emergency and First Aid Procedures
Skin: Wash with soap and water; wash clothes before reuse
Ingestion: If swallowed, Call physician immediatly. Note to Physicians: Remove stomach contents by gastric suction or induce vomitting only directed by medical personnel. Never Give anything by mouth to an unconcious person.
Inhalation: Remove to fresh air if effects occur; consult physician.
Eyes: Irrigate with water for fifteen minutes; consult physician.

Spill or Leak Procedure

Steps to be Taken if Release or Spilled
 Absorb with inert material (sand, vermiculate, Ect.), sweep or scoop yp and put in disposal container. Flush area immediatly with plenty of water; prevent washings from entering waterways.
Waste Disposal Method
 Incinerate in furnace or bury in landfill in accordance with Federal, State & Local Regulations.

Special Protection Information

Respiratory Protection
 NIOSH approved organic vapor respirators are only required when ventilation is inadequate. NIOSH approved air-line respirators eith auxiliary escape air tanks of self-contained breathing apparatus should be used in confined spaces.
Ventilation
 Local mechanical exhaust
Protective Gloves
 Impervious gloves
Eye Protection
 Safety Glasses with side shields.
Other Protective Equipment
 Safety shower and eye bath should be provided. Use coveralls or apron to protect against skin and clothing contamination.

Special Precautions

Precautions to be taken in Storage and handling
 Practice reasonable care and cleanliness
Other Precautions
 Avoid gross contamination of skin. Wash with plenty of soap and water. Use with adequate ventillation. Avoid breathing vapors

Emergency Telephone	Day: 800-878-9593
	Night: 800-878-9593

CAS No.	Hazardous Ingredients	ACGIH	OSHA
28064-14-4	Phenol Novolac Resin	NA	NA
68609-97-2	Alkyl Glycidyl Ether	NA	NA
67762-90-7	Fumed Silica	NA	NA
14808-60-7	Quartz Silica	NA	NA

Physical/Chemical Characteristics

Boiling Point	NA	Vapor Density	NA
Specific Gravity	1.15	Evaporation Rate	NA
Solubility in Water	none		
Vapor Pressure	NA	Melting Point	NA
Appearance & Odor	Straw or colored liquid,sweet characteristic Odor		

Precautions For Safe Handling and use

Flash Point
 485° F (PMCC)
Flammable Limits
 LEL: not available UEL: not available
Extinguishing Media
 Use Water spray, Dry chemical, foam or Carbon Dioxide
Special Fire Fighting Procedures
 Treat as a class B fire.

Reactivity Data

Stability
 Stable
Incompatibility with other materials
 Avoid contact with amines. Keep away from open flame prior to cure.
Hazardous Decomposition Products
 Thermal Decomposition may produce Carbon Monoxide and/or Carbon Dioxide
Hazardous Polymerization
 Will not occur
Conditions To Avoid
 Strong Acids, Amines, Mercatons, Bases (in uncontrollable Amounts)