

# Major Applications for Silicone Foam Control Agents

Dow Corning® Product		Foods				Chemicals					Petrochemicals				Waste Water Treatment		Adhesives/Coatings <sup>2</sup>		Metal Working			Paper/Printing		Textiles				
		Fermentation	Beverages and Preserves	Meat, Poultry and Seafood	Rendering	Distillation	Glycol Scrubbing	Resin Manufacturing	Pesticides, Herbicides and Fertilizers	Detergents	Oil Refining	Gas-Oil Separation	Delayed Cokers	Asphalt	Aromatic and Chlorinated Solvents	Waste Water Treatment	Heating/Cooling Water Treatment	Adhesives and Glues	Latexes	Metal Cleaning and Degreasing	Etching Solutions	Cutting Oils	Paper Coatings	Resin Sizing	Jet Dyeing	Latex Backing	Sizing/Starching	Dry Cleaning
Aqueous	1920 Powdered Antifoam	●	○	○	○										○	○												
	AF Emulsion	○	●					●																				
	B Emulsion		●						●						○		○											
	C Emulsion		●						●																			
	DSP Antifoam Emulsion					○	○		●	●	○				●		○									●	●	
	FG10 Emulsion	●	●	○					●						●	○							●					
	H10 Emulsion					○	○			○					○	○								●			●	
	Y30 Emulsion						○													○								
	1410 Emulsion (formerly DB-110A)						○				○	○			○	○							○	●			●	
	1430 Emulsion (formerly DB-31)					●	○				○	○			○	○	○	○	○	○			○			●	○	
	1510-US Emulsion	●	●	○					●	○	○				●	○												
	1520-US Emulsion	●	●	●					○	○					●	○										○	○	
	2210 Emulsion					○	○								○	●	●	●				○						
	7305 Antifoam					●			●	●					●													
	Aqueous or Nonaqueous	A Compound					○																					
A Compound, Food Grade		○	○		●				●																			
544 Compound						●	○			○											○			●				
1400 Compound (formerly DB-100)						○	●	●		○	●		●	○						●		●						
1500 Compound				●	●		○															○						
Q2-3183A Compound																		●	○	●								
Nonaqueous	HVF 600,000 cs										●	●	●															
	200* Fluid, Food Grade, 350 cSt.			●	●																							
	200* Fluid, 1,000 - 10,000 cSt.							●					●	○														
	200* Fluid, 12,500 - 60,000 cSt.						●				●	●	●	○														
	FS-1265 Fluid, 300 cSt.										○	○		●					○								●	
FS-1265 Fluid, 1,000 - 10,000 cSt.										○	○		●					○								●		

● Primary Recommendation  
○ Alternate Recommendation

<sup>1</sup>All products listed are Dow Corning brand unless otherwise noted.

<sup>2</sup>Refer to separate coating additive literature for antifoam recommendations for paints, inks and coatings. Request Form No. 24-391.

**DOW CORNING**

***WE HELP YOU INVENT  
THE FUTURE.™***

**www.dowcorning.com**

**WARRANTY INFORMATION – PLEASE READ CAREFULLY**

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Dow Corning's products are safe, effective, and fully satisfactory for the intended end use. Dow Corning's sole warranty is that the product will meet the Dow Corning sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. Dow Corning specifically disclaims any other express or implied warranty of fitness for a particular purpose or merchantability, unless Dow Corning provides you with a specific, duly signed endorsement of fitness for use. Dow Corning disclaims liability for any incidental or consequential damages. Suggestions of use should not be taken as inducements to infringe any particular patent.

*Dow Corning* and *200* are registered trademarks of Dow Corning Corporation.  
*WE HELP YOU INVENT THE FUTURE* is a trademark of Dow Corning Corporation.

©2001 Dow Corning Corporation. All rights reserved.

Printed in USA

AGP5680A

Form No. 26-1081-01