



CHLOR*RID International, Inc.

P.O. Box 908 Chandler, AZ 85244

Toll Free 800-422-3217 Office 480-821-0039 Fax 480-821-0364

www.chlor-rid.com

DIRECTIONS

CHLOR*RID[®] LIQUID SOLUBLE SALT REMOVER

DESCRIPTION: CHLOR*RID is a unique organic bonding chemistry which aids in the removal of chlorides, sulfates and surface reacted salts.

HIGH PRESSURE WASHING: CHLOR*RID is added to the water of the pressure washer, usually in a dilution ratio of 1:100. The application rate is dependent on the contamination level and the water quality. Add CHLOR*RID by means of a metering pump or add to a reservoir water supply. A siphon device may be used, but most such devices lack dilution control and positive input. Use potable water or other approved source. A minimum 3000 p.s.i. pressure washer is recommended. Flush washer and lines prior to application. Hold pressure nozzle perpendicular to the surface and no more than 12 inches away to ensure all surfaces are washed with direct high pressure. In areas of deep pitting, slow the wash speed to enable CHLOR*RID to penetrate. Do not rinse. Typical application rate is 300 to 1000 Sq. Ft. per gallon of CHLOR*RID.

HAND WASHING: Use CHLOR*RID DTS[™] (Direct To Surface) according to directions. CHLOR*RID DTS is ready to use direct from the container- no dilution necessary.

WET ABRASIVE BLASTING: Add CHLOR*RID to the system at 1 U.S. gallon per 300-1000 square feet of surface to be blasted using potable water or other approved source. (Dilution ratio of 1:500 typical.) Add CHLOR*RID to rinse water at 1:100 ratio. Always use appropriate safety equipment.

Prior to cleaning or blasting, test surfaces for contaminants with the CHLOR*TEST[™] kit. After cleaning or blasting a small sample area, retest to verify cleanliness. Adjust speed of travel, pressure or dilution as necessary and retest to verify desired cleanliness level is attained.

Due to a wide variety of surface conditions, work environments, weather conditions, etc., these directions are general and may require alterations to better suit individual conditions. Call CHLOR*RID International Inc. for recommendations for a specific project. CHLOR*RID International Inc. assumes no liability for use or misuse of the product inconsistent with its labeling.

WARRANTY: CHLOR*RID International Inc. warrants this product to be identical in chemical and physical properties from batch to batch within the specification limits of the raw materials used in its manufacture.

SAFETY PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. Do not mix with other chemicals. See M.S.D.S. for full precautions before use. This product is intended for professional use only.